



Product Line Brochure



FAITH - VISION - WORK

"We engineer and build what you need." - Since 1927

Table of Contents:	Page:
• Pneumatic Tire Forklift	
• 24-in. Load Center	4 - 7
• 36-in. Load Center	8
• 48-in. Load Center	9 - 10
• Large Capacity	11
• Empty Container Handlers	12
• Loaded Container Handlers	13
• Reach Stackers	14
• Roll-On Roll-Off (RORO)	14
• Removable Counterweight	15
• Cushion Tire Forklift	16 - 17
• Log Stacker	18
• Specialty Trucks	19
• Taylor Leasing	20
• Sudden Service, Inc.	21
• Taylor Genuine OEM Parts	22
• Taylor Safety	23
• Taylor Industrial Tires	24
• Vision Plus	25



Designed, Engineered and Built in the USA.

Backed by 90 years of experience, Taylor Machine Works has become a world-wide operation with sales driven by the professional and aggressive activities of a vast domestic dealer sales, direct sales, and international sales organization.

Taylor Machine Works designs, engineers, and manufactures industrial lift equipment with lift capacities from 16,000-lbs. to 125,000-lbs. Each machine built must pass stringent guidelines, insuring that our customers receive the best possible product.

At the very center of this success has been an unwavering commitment to the key concepts of **FAITH, VISION & WORK** by the members of the Taylor family and employees who collectively form **THE BIG RED TEAM!**

To find out more visit us at... taylorbigred.com



you
can
depend
on
Big Red®

"We engineer and build what you need."

Founder of Taylor Machine Works: W.A. Taylor, Sr.

PNEUMATIC TIRE: 24" Load Center



X-160 & X-175

Rated Cap. 16,000-lbs. (7,257 kg)

Rated Cap. 17,500-lbs. (7,938 kg)

24-in. (610 mm) Load Center

104-in. (2,642 mm) Wheelbase



X-180S, 200S, 220S

X-180S Rated Capacity 18,000-lbs. (8,165 kg)

X-200S Rated Capacity 20,000-lbs. (9,072 kg)

X-220S Rated Capacity 22,000-lbs. (9,979 kg)

24-in. (1,219 mm) Load Center

101-in. (2,565 mm) Wheelbase



X-250S

Rated Capacity 25,000-lbs. (11,350 kg)

24-in. (610 mm) Load Center

110-in. (2,794 mm) Wheelbase



X-250M

Rated Capacity 25,000-lbs. (11,350 kg)

24-in. (610 mm) Load Center

121-in. (3,073 mm) Wheelbase

PNEUMATIC TIRE: 24" Load Center



X-280S

Rated Capacity 28,000-lbs. (12,701 kg)
24-in. (610 mm) Load Center
110-in. (2,794 mm) Wheelbase



X-280M

Rated Capacity 28,000-lbs. (12,701 kg)
24-in. (610 mm) Load Center
121-in. (3,073 mm) Wheelbase



X-300S & 330S

X-300S Rated Cap. 30,000-lbs. (13,608 kg)
X-330S Rated Cap. 33,000-lbs. (14,969 kg)
24-in. (610 mm) Load Center
110-in. (2,794 mm) Wheelbase



X-300M & 330M

X-300M Rated Cap. 30,000-lbs. (13,608 kg)
X-330M Rated Cap. 33,000-lbs. (14,969 kg)
24-in. (610 mm) Load Center
121-in. (3,073 mm) Wheelbase

PNEUMATIC TIRE: 24" Load Center



TX-330SL

Rated Capacity 33,000-lbs. (14,980 kg)
24-in. (610 mm) Load Center
110-in. (2,794 mm) Wheelbase



X-360M

Rated Capacity 36,000-lbs. (16,330 kg)
24-in. (610 mm) Load Center
121-in. (3,073 mm) Wheelbase



X-360L

Rated Capacity 36,000-lbs. (16,330 kg)
24-in. (610 mm) Load Center
138-in. (3,505 mm) Wheelbase

BIG WHEEL: 24" Load Center



TXB-180S & 200S

TXB-180S Rated Cap. 18,000-lbs. (8,165 kg)

TXB-200S Rated Cap. 20,000-lbs. (9,072 kg)

24-in. (610 mm) Load Center

110-in. (2,794 mm) Wheelbase



XB-250M

Rated Capacity 25,000-lbs. (11,350 kg)

24-in. (610 mm) Load Center

121-in. (3,073 mm) Wheelbase



XB-300L & 360L

XB-300L Rated Cap. 30,000-lbs. (13,608 kg)

XB-360L Rated Cap. 36,000-lbs. (16,329 kg)

24-in. (610 mm) Load Center

140-In. (3,556 mm) Wheelbase

PNEUMATIC TIRE: 36" Load Center



XH-180 & XH-180 HYDROSTATIC

Rated Cap. 18,000-lbs. (15,876 kg)
36-in. (914 mm) Load Center
104-in. (6,642 mm) Wheelbase



X-400M & 450M

X-400M Rated Cap. 40,000-lbs. (18,144 kg)
X-450M Rated Cap. 45,000-lbs. (20,412 kg)
36-in. (914 mm) Load Center
156-in. (3,962 mm) Wheelbase



X-450S, 520S & 550S

X-450S Rated Cap. 45,000-lbs. (20,412 kg)
X-520S Rated Cap. 52,000-lbs. (23,587 kg)
X-550S Rated Cap. 55,000-lbs. (24,948 kg)
36-in. (914 mm) Load Center
144-in. (3,658 mm) Wheelbase



X-650S

Rated Capacity 65,000-lbs. (29,483 kg)
36-in. (914 mm) Load Center
164-in. (4,166 mm) Wheelbase

PNEUMATIC TIRE: 48" Load Center



XH-300L & 350L

Rated Capacity 30,000-lbs. (13,608 kg)

Rated Capacity 35,000-lbs. (15,876 kg)

48-in. (1,219 mm) Load Center

148-in. (3,759 mm) Wheelbase



XH-360L

Rated Capacity 36,000-lbs. (16,329 kg)

48-in. (1,219 mm) Load Center

148-in. (3,759 mm) Wheelbase



XH-370M

Rated Capacity 37,000-lbs. (16,783 kg)

48-in. (1,219 mm) Load Center

143-in. (3,683 mm) Wheelbase



XH-400L

Rated Capacity 40,000-lbs. (18,144 kg)

48-in. (1,219 mm) Load Center

155-in. (3,937 mm) Wheelbase

PNEUMATIC TIRE: 48" Load Center



X-520M & 550M

X-520M Rated Cap. 52,000-lbs. (23,587 kg)

X-550M Rated Cap. 55,000-lbs. (24,948 kg)

48-in. (1,219 mm) Load Center

170-in. (4,318 mm) Wheelbase



X-650L

Rated Capacity 65,000-lbs. (29,483 kg)

48-in. (1,219 mm) Load Center

180-in. (4,572 mm) Wheelbase



X-700L

Rated Capacity 70,000-lbs. (31,751 kg)

48-in. (1,219 mm) Load Center

190-in. (4,826 mm) Wheelbase

LARGE CAPACITY: 48" Load Center



X-800S & 900S

X-800S Rated Cap. 80,000-lbs. (36,287 kg)
X-900S Rated Cap. 90,000-lbs. (40,823 kg)
48-in. (1,219 mm) Load Center
195-in. (4,953 mm) Wheelbase



X-900M

Rated Capacity 90,000-lbs. (40,824 kg)
48-in. (1,219 mm) Load Center
215-in. (5,461 mm) Wheelbase



X-800L & 925L

X-800L Rated Cap. 80,000-lbs. (36,287 kg)
X-925L Rated Cap. 92,500-lbs. (41,957 kg)
48-in. (1,219 mm) Load Center
225-in. (5,715 mm) Wheelbase



XH-925L

Rated Cap. 92,500-lbs. (41,957 kg)
48-in. (1,219 mm) Load Center
225-in. (5,715 mm) Wheelbase

CONTAINER HANDLERS: Empty



XEC-155/6

Rated Capacity for 9.5-ft. (2.9 m) High Containers:
15,000-lbs. (6,804 kg) / 5-high Stacking
Rated Capacity for 8.5-ft. (2.6 m) High Containers:
15,000-lbs. (6,804 kg) / 6-high Stacking
100-in. (2,540 mm) Load Center
150-in. (3,810 mm) Wheelbase



XEC-205/6

Rated Capacity for 9.5-ft. (2.9 m) High Containers:
20,000-lbs. (9,072 kg) / 6-high Stacking
Rated Capacity for 8.5-ft. (2.6 m) High Containers:
20,000-lbs. (9,072 kg) / 7-high Stacking
103-in. (2,616 mm) Load Center
180-in. (4,572 mm) Wheelbase



XEC-206/7

Rated Capacity for 9.5-ft. (2.9 m) High Containers:
20,000-lbs. (9,072 kg) / 6-high Stacking
Rated Capacity for 8.5-ft. (2.6 m) High Containers:
20,000-lbs. (9,072 kg) / 7-high Stacking
103-in. (2,616 mm) Load Center
180-in. (4,572 mm) Wheelbase



XEC-207/8

Rated Capacity for 9.5-ft. (2.9 m) High Containers:
20,000-lbs. (9,072 kg) / 7-high Stacking
Rated Capacity for 8.5-ft. (2.6 m) High Containers:
20,000-lbs. (9,072 kg) / 8-high Stacking
103-in. (2,616 mm) Center Of Load
180-in. (4,572 mm) Wheelbase

CONTAINER HANDLERS: Loaded



XLC-975

Rated Capacity At 97-in. (2,464 mm) Center of Load
 90,000-lbs. (40,824 kg) / 2-high Stacking
 80,000-lbs. (36,288 kg) / 5-high Stacking
 Rated Capacity At 106-in. (2,692 mm) Center of Load
 82,000-lbs. (37,195 kg) / 2-high Stacking
 75,000-lbs. (34,020 kg) / 5-high Stacking
 236-in. (5,994 mm) Wheelbase



XLC-976

Rated Capacity At 97-in. (2,464 mm) Center of Load
 90,000-lbs. (40,824 kg) / 2-high Stacking
 80,000-lbs. (36,288 kg) / 6-high Stacking
 Rated Capacity At 106-in. (2,692 mm) Center of Load
 82,000-lbs. (37,195 kg) / 2-high Stacking
 75,000-lbs. (34,020 kg) / 6-high Stacking
 236-in. (5,994 mm) Wheelbase



Exclusive Distribution Only

XLC-974

Rated Capacity At 97-in. (2,464 mm) Center of Load
 90,000-lbs. (40,824 kg) / 2-high Stacking
 85,000-lbs. (38,555 kg) / 3 and 4-high Stacking
 Rated Capacity At 106-in. (2,692 mm) Center of Load
 82,000-lbs. (37,195 kg) / 2-high Stacking
 80,000-lbs. (36,287 kg) / 3 and 4-high Stacking
 236-in. (5,994 mm) Wheelbase



Exclusive Distribution Only

XTCP-900

Rated Capacity At 97-in. (2,464 mm) Center of Load
 90,000-lbs. (40,824 kg) / 2-high Stacking
 80,000-lbs. (36,288 kg) / 6-high Stacking
 Rated Capacity At 106-in. (2,692 mm) Center of Load
 82,000-lbs. (37,195 kg) / 2-high Stacking
 75,000-lbs. (34,020 kg) / 6-high Stacking
 236-in. (5,994 mm) Wheelbase

REACHSTACKERS:



XRS-9972

Rated Container Capacity 99,000-lbs. (45 t)
First Row / 4-high Stacking 9.5-ft. (2.9 m)
Rated Container Capacity 90,400-lbs. (41 t)
First Row / 5-high Stacking 9.5-ft. (2.9 m)
258-in. (6,550 mm) Wheelbase



XRS-9985

ISO & WTP Rated Container Cap. 99,000-lbs. (45 t)
First Row / 4-high Stacking 9.5-ft. (2.9 m)
Rated Container Capacity 90,400-lbs. (41 t)
First Row / 5-high Stacking 9.5-ft. (2.9 m)
280-in. (7,112 mm) Wheelbase

ROLL-ON ROLL-OFF: RORO



X-620RR

Rated Capacity 62,000-lbs. (28,123 kg)
Load Center 48-in. (1,219 mm)
Wheelbase 167-in. (4,242 mm)



X-720RR

Rated Capacity 72,000-lbs. (32,659 kg)
48-in. (1,219 mm) Load Center
185-in. (4,699 mm) Wheelbase

REMOVABLE COUNTERWEIGHT:



TX-550RC

55,000-lbs (25,000 kg) @ 36-in (915 mm) L.C.
48,000-lbs (21,800 kg) @ 48-in (1,220 mm) L.C.
Removable Counterweight 30,000-lbs (13,608 kg)
Transport Weight w/o Counterweight 46,000-lbs
(20,866 kg)
144-in. (3,658 mm) Wheelbase



X-925RC

Rated Capacity 92,500-lbs. (41,958 kg)
Removable Counterweight 40,000-lbs. (18,144 kg)
Transport Weight w/o Counterweight 84,000-lbs.
(38,102 kg)
48-in. (1,219 mm) Load Center
225-in. (5,715 mm) Wheelbase



X-1000RC

Rated Capacity 100,000-lbs. (45,454.5 kg)
Removable CWT 45,000-lbs. (20,412 kg)
Transport Weight w/o CWT 95,000-lbs. (43,091 kg)
36-in. (914.4 mm) Load Center
195-in. (4,953 mm) Wheelbase

CUSHION TIRE:

See Product Specification Sheets for Alternate Load Centers & Rated Capacities for the Models Below.



XC-180S, 200S 220S

XC-180S Rated Cap. 18,000-lbs. (8,165 kg)
XC-200S Rated Cap. 20,000-lbs. (9,072 kg)
XC-220S Rated Cap. 22,000-lbs. (9,979 kg)
24-in. (610 mm) Load Center
80-in. (2,032 mm) Wheelbase

(SL models have shorter overall height of 88")



XC-250M & 300M

XC-250M Rated Cap. 25,000-lbs. (11,340 kg)
XC-300M Rated Cap. 30,000-lbs. (13,608 kg)
24-in. (610 mm) Load Center
88-in. (2,235 mm) Wheelbase

(ML models have shorter overall height of 88")



XC-350L

Rated Cap. 35,000-lbs. (15,876 kg)
24-in. (610 mm) Load Center
98-in. (2,489 mm) Wheelbase



THC-250S & 300S

THC-250S Rated Cap. 25,000-lbs. (11,340 kg)
THC-300S Rated Cap. 30,000-lbs. (13,608 kg)
24-in. (610 mm) Load Center
94-in. (2,388 mm) Wheelbase

CUSHION TIRE:



THC-400L

Rated Capacity 40,000-lbs. (18,144 kg)
30-in. (762 mm) Load Center
110-in. (2,794 mm) Wheelbase



THC-500L

Rated Capacity 50,000-lbs. (22,680 kg)
30-in. (762 mm) Load Center
110-in. (2,794 mm) Wheelbase



XHC-600L

Rated Capacity 60,000-lbs. (27,216 kg)
36-in. (914 mm) Load Center
125-in. (3,175 mm) Wheelbase

LOG STACKER:



TXLS-1000

Rated Capacity 100,000-lbs. (45,360 kg)

Load Center 48-in. (1,219 mm)

Wheelbase 288-in. (7,315 mm)

SPECIALTY TRUCKS:



TTX-200

Rated Drawbar Pull 20,000-lbs. (89 kN)
95-in. (2,413 mm) Wheelbase



PTX-500

Rated Capacity 55,000-lbs. (24,948 kg)



TX4-250, 300 & 360

TX4-250 Rated Capacity 25,000-lbs. (11,340 kg)
TX4-300 Rated Capacity 30,000-lbs. (13,608 kg)
TX4-360 Rated Capacity 36,000-lbs. (16,330 kg)
24-in. (610 mm) Load Center
132-in. (3,353 mm) Wheelbase



"Offering Leasing Solutions for Industrial Equipment"

Taylor Leasing Corporation, a subsidiary of The Taylor Group of Companies, provides competitive finance and lease solutions for your Taylor equipment material handling needs. Our mission is to be the preeminent financial service provider to our global customer base, delivering the highest quality products and services. Taylor Leasing can provide incentives and opportunities beyond the reach of third party finance companies.

Our goal is to structure a financial product that improves your profit with reduced operating cost by increasing up-time and offering a wide range of financial products to fit the specific needs of your business.

Taylor Leasing offers over 100 different financial structures within the main product categories of:

- **Operating Lease** - A financial choice which provides use of equipment for extended period of time with a low monthly operating cost.
- **Loan/Installment Sales Contract** - This choice is for those that prefer ownership of equipment over extended period of time.
- **Finance Lease** - This type of lease offers flexibility in payments with equipment ownership options at the end of the lease term.

For more information contact:

Stephen Arnett

Email: sarnett@taylorbigred.com

Phone: (662) 773-3421 Ext. 400

Fax: (662) 773-9146

Or visit us at:

www.taylorbigred.com/Equipment-Leasing.html



Your #1 Source for Genuine Taylor Parts and Forklift Service

Sudden Service, Inc. provides exclusive worldwide distribution of Genuine Taylor OEM parts and forklift service for equipment designed, manufactured, and marketed by Taylor Machine Works, Inc. Backed by a network of parts and service centers, nationwide dealer support organizations, and factory trained service technicians, SSI is committed to providing the best aftermarket support in the industry.

Sudden Service also offers training seminars for its service technicians on a regular basis, ensuring the best possible service to Taylor Machine Works' customers.

With major component parts from Cummins®, AxleTech™ International, Kessler®, and Dana®, to name a few, Sudden Service will help you keep your Taylor equipment up and running. Expect courteous, efficient assistance and expedient replacement parts shipments from our staff of trained sales representatives.

Sudden Service, Inc.
Corporate Office
649 North Church Ave
Louisville, MS 39339

Phone: (662) 773-8056
Parts Fax: (662) 773-9160
Service Fax: (662) 773-9157
www.suddenserviceinc.com



Genuine Taylor Dealers understand the need for Genuine Taylor Parts.

Sudden Service, Inc. has its own Distribution & Operation Center (DOC) complete with a fully equipped fabrication shop as well as a fully stocked warehouse serving all Taylor service parts.

OEM Parts Support:

You Can Depend On Big Red® is a personal and collective commitment from the Taylor "**Big Red**" Team to every customer. Customer needs and expectations are priorities for Taylor engineering, manufacturing, marketing, and service organizations.

Sudden Service, Inc.® and our worldwide Taylor dealer network are ready to respond to your requests for support requirements twenty-four hours a day, seven days a week!

For more information or to find your nearest service center visit:

www.suddenserviceinc.com

When Failure Is Not An Option... Use Only Genuine Taylor Parts.



TAYLOR SAFETY

Taylor Machine Works, Inc. provides many safety materials for use in conjunction with Taylor equipment. It is imperative that not only the operator be familiar with the safety materials, but also that operations directors and other safety officials utilize the safety materials provided to ensure a safe and ergonomically designed work environment. Taylor Machine Works, Inc.'s commitment to building the safest products and providing good safety materials, in conjunction with the employers commitment and responsibility to provide well-trained operators and safe work environments, will result in a Win, Win situation!

Safety Check Video Training Program

The Safety Check Video Training Program consists of 5 modules on 2 high quality DVDs. These DVDs are only available upon request. For more information or to request a copy of the Safety Check Video Training Program DVDs please contact Julia Love at 662-773-3421.

Safety Training

Under the regulations of OSHA and ANSI, it is the responsibility of the employer to assure that those individuals assigned responsibilities in operation of industrial trucks be properly trained. Through the combined efforts of Taylor Machine Works, Inc. and Industrial Training Systems, Inc., you can be assured that your operators are properly trained to complete their assigned tasks. For more information contact: **Jim Shephard**

Industrial Training Systems, Inc.

P.O. Box 341033
2838 Stage Center Cove
Bartlett, TN 38184-1033

Phone: 901-382-5507
FAX: 901-382-2811

www.shephardsystems.com



Premium Industrial Lift Truck Tire

Taylor Industrial Tires offers a wide selection of Super Grip tires for many industrial applications. From lift trucks to construction equipment, skid steer loaders to trenchers, golf carts to wheel barrows, Taylor Industrial Tires has the tire for you.

After Taylor Machine Works saw how Super Grip tires performed on its lift trucks, Taylor Industrial Tires was formed to pass this exceptional product on to you, the consumer. Taylor Machine Works has been in the business of manufacturing industrial material handling equipment for over 90 years. Both Taylor Machine Works and Super Grip are known for their outstanding products.



With deeper treads, rim guard protection, and full dimension sizing, Super Grip tires are fast becoming the tire of choice. Super Grip uses more rubber in the construction of its tires, resulting in longer wear and more gripping power throughout the life of its tires.

Tough enough to be approved by & used on Taylor Lift Trucks!!!

Taylor Exclusive Tires - Sold only through Taylor Industrial Tires and its authorized dealers.

Sudden Service, Inc.
649 North Church Ave.
Louisville, MS 39339-2022

Phone: (662) 773-8056
Fax: (662) 773-9160

www.taylorindustrialtires.com

VISION™

PLUS

POWERED BY MOBILEYE®

The Next Generation Pedestrian Detection Aid

Vision Plus™ provides the operator of mobile equipment with real-time information concerning the location and tracking of pedestrians in the operating area around the equipped vehicle. Mobileye's unique artificial vision technology enables the Vision Plus™ system to ignore non-pedestrian obstacles significantly reducing the number of alarms to the operator and to bystanders. This functionality, unique to the Vision Plus™ system, ensures that only the most important information is provided to the operator. Ergonomic display of information both audibly and visually, industrial grade camera enclosures and hardware, and state of the art sensor-less, tag-less technology combine to provide a pedestrian detection aid that will add to the operator's practice of clearing the area with direct vision.

- Powder coated for long lasting finish
- O-ring sealed connector
- Rugged construction, designed for use in industrial environments
- Cover with drip edge to reduce water dripping in front of the camera
- Level 2 Alert
- Audible alarm with adjustable volume
- Enclosure is sealed to withstand damage from outdoor elements
- Enclosure is cast aluminum with integrated heat sink
- LED indicators provide a bright visual alert to the operator
- Fully encapsulated electronics for increased durability



Can't find a system to fit your application?

Vision Plus™ Pro offers a fully customizable solution to meet your unique requirements. Vision Plus™ Pro can be configured for specialty applications including custom display of information, data logging, on board maintenance tools, and custom engineering. Your Certified Vision Plus dealer can discuss with you your specialty application.

www.visionplussafety.com

NOTES:

1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	

NOTES:

1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	



Taylor Machine Works, Inc.
3690 N. Church Ave.
Louisville, MS 39339
www.taylorbigred.com

03/20/17